## 

## **AMBUSH**



**HEAVY DUTY** CONSTRUCTION



PAN / TILT



LOCKING 1.5" TO 3" GRIP



**USER FRIENDLY** 

OFFSET GRIP



**ADJUSTABLE** TAPERED GRIP



**PROTECTIVE** PADDING





MOUNTS ON LOCKED IN PLACE FIREARM SITS WHEN SET ABOVE THE LEDGE





**PICK UP AND MOVE EASILY** 



**ADJUST BIPOD** TO FIT LEDGE



KJ85005K



D

MOUNTING

AMBUSH MATERIAL

WEIGHT (LBS/GR)



<b>AMBUSH</b>	
SYSTEM	

TECHNICAL	SYSTEM
SPECIFICATIONS	KJ85005K
DIMENSIONS (IN/MM)	12.24 x 4.17 x 11.9 / 311 x 106 x 302
VISE WIDTH RANGE (IN/MM)	1.5 - 3 / 40 - 71
PAN ROTATION ANGLE	360°
VERTICAL ROTATION ANGLE	87° DOWN, 21° UP
MOUNTING	PLACED ON LEDGE
AMBUSH MATERIAL	ALUMINUM
WEIGHT (LBS/GR)	4.35 / 1688
KIT INCLUDES	REAPER GRIP AMBUSH ASSEMBLY BIPOD

INCLUDES CAMERA THREAD ADAPTER

TECHNICAL	ASSEMBLY	
SPECIFICATIONS	KJ85005	
DIMENSIONS (IN/MM)	12.24 x 4.17 x 3.4 / 311 x	

ANDUICH

INCLUDES CAMERA THREAD ADAPTER AND SOCKET HEAD SCREW

3/8" - 16 THREADED HOLE

**ALUMINUM** 

1.22 / 553

106 x 86